

## Interior Latex Sand-Finish Paint

\*Sand Finish • 2250

### Product Description

Sun-Tex Interior Latex Sand-Finish Paint is a quality professional grade coating specifically formulated to provide texture and paint in one step. Suitable for use on a variety of properly prepared substrates including concrete, masonry, drywall, wood, brick, plaster and stucco. **This product is for interior use only. \*SPECIAL ORDER ONLY**

### Recommended Substrates

- Drywall, wallboard, and plaster
- Wood trim, molding, and windows
- Wood & fiberglass doors
- Primed metals
- Numerous other substrates

### Product Features

- Excellent coverage
- Helps hide minor surface imperfections
- Low odor
- Soap and water clean up

### Product Limitations

This product is for use on properly prepared above grade vertical substrates. Do not apply to horizontal surfaces or areas that come in constant contact with moisture or standing water.

Available bases | 2250: White Base

**Application:** Brush & Roller - Small areas only.  
Specialty spray is equipment for textured coatings

Dry time @ 50% RH\*: 2 - 4 HRS to touch  
4 - 6 HRS to recoat

\*dry times listed may vary according to the relative humidity, temperature, film build, color and air movement of the application environment.

Flash Point: NonFlammable >200°F

Clean Up: Soap and water

### Compliance

This product are VOC compliant based on limits provided by EPA, CARB, MPI GPS-1 & GPS-2 and SCAQMD.

### Product Data

Product Type: **Waterborne Vinyl Acrylic**

Gloss @60°: **2250**  
1 - 5

Wt Solids ±2%: 63%

Vol Solids ±2%: 46%

Wet Film Mils: 8.0 - 10.0

Dry Film Mils: 3.7 - 4.6

Coverage / Gal \* 160 - 200

\* coverage and wet and dry millage will vary by substrate type and porosity.

VOC gm p/L \*\*: <50

\*\* less exempt solvents and before the addition of colorant

Viscosity KU ±5: 120

### Surface Preparation

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a properly fitted NIOSH approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**General Surface Preparation:** The performance of this product is dependent on the integrity and soundness of the substrate. All surfaces should be clean and free of any dirt, rust, grease, mill oils, mill scale, efflorescence, organic growth, mildew or other contaminants that might adversely affect the adhesion and performance of this product. Any failed or deteriorated caulk or patching compound should be removed and replaced. Unpainted surfaces should be primed in accordance with manufacturer's recommendations. New precast and tilt-wall concrete must be cleaned to remove all form release agents, see manufacturers data sheet for cleaning methodology. Also, a successful water-break test is recommended every 1000 sq ft.

See **1B-08-S Painting Tilt Wall Concrete** for additional information.

**New Concrete, Stucco and Masonry Surfaces:** Prime with SunFlex 3850 Concrete & Masonry Primer once the pH is less than 13. Fill CMU or brick with FortiFill 3550 Masonry Filler. For optimal performance, new concrete, stucco, and block mortar joints should cure at least 30 days with a pH of 10 or less.

**Application:** Mix thoroughly prior to use and ensure product remains mixed during the application process. Product may be applied by brush or roller in small areas but is primarily applied by spray equipment designed for aggregate coatings. Apply coating evenly by maintaining a "wet edge" to prevent lap marks, avoid starting and stopping, apply to a natural break to prevent lap marks.

**Thinning:** Thinning is not required and not recommended unless approved by the manufacturer in writing.

**Brush:** Use nylon or polyester bristle brushes.

**Roller:** Use a 3/4" to 1-1/4" synthetic or lamb's wool cover.

**Spray Application:** Use a texture spray unit similar to Graco President, 10:1 pump or Graco GM 1030 or other approved texture sprayers with a minimum of 1000 psi of pressure or 3.0 gpm, with a 3 - 12 mm spray tip. For fine finish texture, backrolling may be required. If so, backroll only in one direction.

**Clean Up:** Tools should be cleaned immediately after use with warm, soapy water. Spray equipment should be flushed thoroughly after each use.

**Dry Time and Curing:** Dry to touch in 2-4 hours and recoat in 4-6 hours. Do not use when air surface or product temperatures are below 50°F or above 100°F. Cleaning of the finish coating should not occur until a minimum of 30 days after the initial application.

**Clean Up:** Minor spills and spatters should be immediately cleaned with soap and water, as well as any painting tools and airless spray equipment. More serious spills should be contained and removed with inert absorbent material. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations.

**Sizes Available:** 5 gallon pails only.

**Colors Available:** Most light to mid-tone colors with a light reflectance value (LRV) of greater than 50-60% are possible. For color consistency, and dark, deep, or vibrant colors topcoat with Florida Paints SunHide Acrylic Wall & Trim Paint - satin or semi-gloss finish or approved acrylic paint approved by the manufacturer in writing.

**SAFETY - WARNING!** May cause an allergic skin reaction. **CAUTIONS: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY! USE ONLY WITH ADEQUATE VENTILATION!** Avoid prolonged contact with skin, and breathing of dust, vapors, or spray mists. Avoid contact with eyes and wear eye protection. Wear a NIOSH approved respirator to avoid inhalation of the dust and fumes and wear clothing designed to prevent skin contact. Wash skin thoroughly after handling. Close container after each use and store in a secure, shaded, and dry location. **First Aid:** Wash skin thoroughly with plenty of warm soap and water. In case of eye contact immediately flush with plenty of water for 15 minutes and get medical attention immediately. If you experience difficulty breathing leave area to obtain fresh air. If continued difficulty is experienced get medical attention immediately. If swallowed do not induce vomiting and get medical attention immediately. If skin irritation or rash occurs get medical advice/attention.

### Storage and Disposal

Product should be kept from freezing temperatures & stored in a cool, dry location. Refer to your local city or county government for instructions on disposal options.

Florida Paints believes the technical data represented in this technical bulletin to be current and up to date. However, Florida Paints makes no warranties or guarantees either expressed or implied. Florida Paints claims no responsibility from damages incurred from use by either the purchaser or user of the product.

PDS 2250 2303



Please excuse the small print used on this document but most paint company datasheets are two pages long. By squeezing all this information on one page we are doing our part to save a few trees.

**Florida Paints and Coatings, LLC**

78 3rd Street | Winter Garden, Florida 34787  
407.986.1000 | [info@FloridaPaints.com](mailto:info@FloridaPaints.com) | [FloridaPaints.com](http://FloridaPaints.com)