

**SnapDry™****Interior-Exterior Waterbased Semi-Gloss**

A71W00051 Extra White, A71W00053 Deep Base, A71T00054 Ultradeep Base

**SHERWIN  
WILLIAMS®****CHARACTERISTICS**

**SnapDry™ Interior-Exterior Semi-Gloss Waterbased Door & Trim Paint** is designed for use on doors, trim, windows, and shutters. SnapDry is resistant to dirt, fingerprints and UV weathering. With Quick Dry Technology, you can close doors sooner and not worry about it sticking.

**VinylSafe™ Paint Colors** allows the freedom to choose from 100 color options, including a limited selection of darker colors formulated to resist warping or buckling when applied to a sound, stable vinyl substrate.

**Color:** Most Colors  
To optimize hide and color development, always use the recommended P-Shade primer

**Coverage:** 350-400 sq.ft. per gallon  
@ 4 mils wet; 1.4 mils dry  
7.0 wet mils maximum per coat

**Drying Time, @ 77°F, 50% RH:**

Touch: 1 Hour  
Recoat: 2 Hours

Drying and recoat times are temperature, humidity, and film thickness dependent

**Finish:** 45-55 units @ 60°

**Tinting with CCE only:**

| Base:          | oz. per gallon | Strength: |
|----------------|----------------|-----------|
| Extra White    | 0-6            | SherColor |
| Deep Base      | 4-14           | SherColor |
| Ultradeep Base | 10-12          | SherColor |

**Extra White A71W00051**

(may vary by color)

**V.O.C. (less exempt solvents):**

less than 50 grams per litre; 0.42 lbs. per gallon  
As per 40 CFR 59.406

**Volume Solids:** 34 ± 2%

**Weight Solids:** 46 ± 2%

**Weight per Gallon:** 9.75 lbs

**Flash Point:** N/A

**Vehicle Type:** Acrylic Latex

**Shelf Life:** 36 months unopened

**WVP Perms (US):** 32.09 grains/(hr ft<sup>2</sup> in Hg)

**Mildew Resistant**

This coating contains agents which inhibit the growth of mildew on the surface of this coating film.

**COMPLIANCE**

As of 07/29/2020, Complies with:

|                            |     |
|----------------------------|-----|
| OTC                        | Yes |
| OTC Phase II               | Yes |
| SCAQMD                     | Yes |
| CARB                       | Yes |
| CARB SCM 2007              | Yes |
| Canada                     | Yes |
| LEED® v4 & v4.1 Emissions  | No  |
| LEED® v4 & v4.1 V.O.C.     | Yes |
| EPD-NSF® Certified         | No  |
| MIR-Product Lens Certified | No  |
| MPI®                       | No  |

**APPLICATION**

Surface, air, and substrate temperatures must be within a range of 50°F-90°F. Relative humidity must be between 40%-70%. Paints dry faster in higher temperatures, lower humidity, and when exposed to direct sunlight. When possible, paint in early morning or late afternoon. You may also be able to avoid direct sunlight while painting by opening the door into the home.

No reduction needed.

**Brush:**

Purdy XL, Purdy Clearcut 2-2 1/2 inch

**Roller:**

Purdy Jumbo Soft Woven 3/8-1/2 inch  
Contractor Series Mohair 3/16 inch

For specific brushes and rollers, please refer to our Brush and Roller Guide on [sherwin-williams.com](http://sherwin-williams.com)

**Spray—Airless**

Pressure 1500-2000 p.s.i.  
Tip .011-.015 inch

**APPLICATION TIPS**

Make sure product is completely agitated (mechanically or manually) before use.

When using **SnapDry** paint make sure any paint drips are smoothed out with a brush or roller within 5-10 minutes of application. If drips are noticed after 10 minutes of application, allow 1-2 hours to dry and use a putty knife or razor to remove the affected area. Lightly sand area if needed and repaint.

Allow **SnapDry** paint to dry before applying a second coat. When second coat is dry, remove all painter's tape, re-install your door hardware. While making brush or roller strokes, make sure the fresh paint you are overlapping is still wet. This will help you to avoid paint streaks.

**SPECIFICATIONS**

Apply 2 topcoats of **SnapDry** directly over existing properly prepared, interior or exterior coatings, or properly primed new interior or exterior surfaces as directed below.

**Interior:****Wood**

1 coat Premium Wall & Wood Primer

**Interior & Exterior:****Aluminum & Galvanized Steel**

1 coat All Surface Enamel Latex Primer

**Steel**

1 coat All Surface Enamel Latex Primer

**Exterior:****Wood, Composition Board**

1 coat Exterior Oil-Based Wood Primer  
or Exterior Latex Wood Primer

**Plywood**

1 coat Exterior Latex Wood Primer

**\*Vinyl Trim or Shutters**

1 coat Multi-Purpose Latex Primer

Other primers may be appropriate.

When repainting involves a drastic color change, a coat of primer will improve the hiding performance of the topcoat color.

Due to the fast dry nature of **SnapDry**, all quick dry waterbased and alkyd primers (those stating to recoat in as little as 1 hour) should be allowed to dry a minimum of 4 hours in good drying conditions. All other primers, follow the primer recommendations.

**SURFACE PREPARATION**

**WARNING!** Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (**NIOSH** approved) and proper containment and cleanup. For more information, call the National Lead Information Center at **1-800-424-LEAD** (in US) or contact your local health authority.

Remove all surface contamination by washing with an appropriate cleaner, rinse thoroughly and allow to dry. Existing peeled or checked paint should be scraped and sanded to a sound surface. Glossy surfaces should be sanded dull. Stains from water, smoke, ink, pencil, grease, etc. should be sealed with the appropriate primer/sealer. Recognize that any surface preparation short of total removal of the old coating may compromise the service length of the system.

**Aluminum and Galvanized Steel:**

Wash to remove any oil, grease, or other surface contamination. All corrosion must be removed with sandpaper, wire brush, or other abrading method. Prime with All Surface Enamel Latex Primer.

**Caulking:**

Gaps between walls, ceilings, crown moldings, and other interior trim can be filled with the appropriate caulk after priming the surface.

**Steel:**

Remove all corrosion by abrading the surface. Prime bare steel the same day as cleaned with All Surface Enamel Latex Primer.

**SURFACE PREPARATION****Mildew:**

Prior to attempting to remove mildew, it is always recommended to test any cleaner on a small, inconspicuous area prior to use. Bleach and bleaching type cleaners may damage or discolor existing paint films. Bleach alternative cleaning solutions may be advised.

Mildew may be removed before painting by washing with a solution of 1 part liquid bleach and 3 parts water. Apply the solution and scrub the mildewed area. Allow the solution to remain on the surface for 10 minutes. Rinse thoroughly with water and allow the surface to dry before painting. Wear protective eyewear, waterproof gloves, and protective clothing. Quickly wash off any of the mixture that comes in contact with your skin. Do not add detergents or ammonia to the bleach-water solution.

**Wood:**

Clean the surface thoroughly then sand any exposed wood to a fresh surface. Patch all holes and imperfections with a wood filler or putty and sand smooth. All new and patched areas must be primed with appropriate primer. Exterior: Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these bare woods, it may show some staining. If staining persists, spot prime severe areas with 1 coat of Exterior Oil-Based Wood Primer prior to using.

**\*Vinyl or other PVC Building Products :**

Clean the surface thoroughly by scrubbing with warm, soapy water. Rinse thoroughly, prime with appropriate white primer. Do not paint vinyl with any color darker than the original color or having a Light Reflective Value (LRV) of less than 56 unless VinylSafe® Paint Colors are used. If VinylSafe Paint Colors are not used the vinyl may warp. Follow all painting guidelines of the vinyl manufacturer when painting. Only paint properly installed vinyl siding. Deviating from the manufacturer's painting guidelines may cause the warranty to be voided.

**CAUTIONS**

Non-photochemically reactive.  
Protect from freezing.

Before using, carefully read **CAUTIONS** on label

**CRYSTALLINE SILICA:** Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (**NIOSH** approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (**NIOSH** approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. **FIRST AID:** In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. **DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE.** Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. **WARNING:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. **DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

HOTW 07/29/2020 A71W00051 13 46  
SP, FRC

**CLEANUP INFORMATION**

Clean spills, spatters, hands and tools immediately after use with soap and warm water. After cleaning, flush spray equipment with a compliant cleanup solvent to prevent rusting of the equipment. Follow manufacturer's safety recommendations when using solvents.

Do not pour unused contents down the drain. Consult with local authorities for method of disposal and recycling.