# EXQUISITE®
## Interior Semi-Gloss Paint
## EXQT50

APPLY A HIGHER STANDARD®

URETHANE ACRYLIC™ | Formulated without Ethylene Glycol or Any Other TAC/HAP Chemical | EG-FREE® | MILDEW INHIBITOR | CERTIFIED BY green wise® COATINGS RESEARCH GROUP INCORPORATED

≤ 50 g/L VOC**

**EXQUISITE® Semi-Gloss** is a deluxe interior, ultra-low VOC, urethane modified acrylic paint meticulously engineered to provide best-in-class hide, scuff, mar, stain and chemical resistance. **EXQUISITE Semi-Gloss** is easy to apply and is ideal for use on high-end custom residential and premier commercial projects where exceptional performance and refined results are required.

## PRODUCT INFORMATION

**SOLVENT TYPE:** Waterborne | **RESIN TYPE:** Urethane acrylic

**FINISH** (ASTM D523): Semi-Gloss: 40-50% on a 60º meter

**COLORS:** All colors can be special ordered or store mixed.

**TINT BASES:** L Tintable White, M Medium, U Ultra Deep

**VISCOSITY@77ºF/25ºC** (ASTM D 562): 95-105 KU

**MAXIMUM VOC CONTENT**
50 g/L (by ASTM Test Method D 6886)

**MAXIMUM RAVOC** (Reactivity-Adjusted VOC)
40 g/L

**SOLIDS BY VOLUME** (ASTM D 2697)
36.8% ± 2%

**SOLIDS BY WEIGHT**
50.7 ± 2%

**WEIGHT PER GALLON** (ASTM D 1475)**:** 10.46 lbs.

**COMPOSITION BY WEIGHT**

| **Pigment–25.9%** | | **Vehicle–74.1%** | |
|---|---|---|---|
| *Prime pigments | 24.8% | Resin solids | 20.9% |
| Reinforcing pigments | 1.1% | Water & additives | 53.2% |

***Prime pigments include all pigments directly adding to the hiding power of this paint.**

**RECOMMENDED FILM THICKNESS PER COAT**
Wet: 4.2 mils Dry: 1.5 mils

**PERFORMANCE SPECIFICATION**

Scrubbability Results: >4000 cycles | **ASTM D2486; no shim**
Block Resistance Results: Excellent | **ASTM D4946-08; Room Conditioned**
Washability Reults: Pass (9.8) | **ASTM D4828; avg of 5 stains**
Cleansability Results: Coffee <2.0 Δe, Nigrosin <1.0 Δe, Graphite <1.5 Δe | **MPI Method**

**PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS**
Approximately 350-425 sq. ft. per gallon, depending on surface conditions and application techniques.

**THINNING RECOMMENDATION:** This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

**AVERAGE DRY TIME@77ºF/25ºC** (ASTM D 1640)
To touch: 1–2 hours Recoat: Spray 2 hours, Brush & Roll 6 hours
For best results wait 24 hours to recoat with brush & roll. Dry times and recoat time are temperature, humidity and film thickness dependent.

**APPLICATION EQUIPMENT:** Brush, roller, airless spray

| AIRLESS SPRAY | BRUSH | ROLLER |
|---|---|---|
| **PRESSURE:** 1800-2500 psi<br>**TIP:** .013"-.015" | Nylon/Polyester | Smooth Surfaces: ¼" - ⅜" nap<br>Semi-Smooth Surfaces: ⅜" - ½" nap |

**PACKAGING:** Quart, one-gallon, five-gallon containers

**STORAGE:** Store in a dry area. Protect from freezing. Protect from temperatures above 110ºF for extended periods of time. Extreme temperatures may cause paint to become unusable. See *Paint Storage Best Practices* Technical Bulletin at dunnedwards.com for more information.

**CLEANUP:** Warm, soapy water

**DISPOSAL:** For information on local options to dispose of unwanted left-over paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com. **Do not mix with other products.**

| CONFORMS TO: | |
|---|---|
| • ARB 2007/2020 SCM & CALGreen 2022<br>• CA Section 01350<br>• LEED v4/4.1<br>• SCAQMD Rule 1113 | • CA Extended Producer Responsibility<br>• MIR, HPD<br>• CRGI Green Wise Certified |

**SAFETY DATA SHEET:** Available at www.dunnedwards.com

**SURFACE PREPARATION: EXQUISITE** Semi-Gloss is self priming on most surfaces. For previously painted surfaces that are properly repaired as needed, one (1) coat may be sufficient. For properly prepared new surfaces, two (2) coats are typically required. All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

**SPECIAL INSTRUCTIONS**

- **CAUTION!** Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Wear a NIOSH-approved N100 particulate filter mask to avoid breathing dust. Use a HEPA vacuum for cleanup, and finish by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or / asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- This paint contains a preservative that inhibits the growth of mildew on the surface of the dry paint film.
- On Level 4 and 5 Drywall Finishes, use **VINYLASTIC® Plus (VNPL00)** thinned with 10% of clean water (3/4 pints per gallon or 1/2 gallon per 5-gallons) for best penetration.
- Do not apply when the air or surface temperature is below 50ºF.

# EXQUISITE®
## Interior Semi-Gloss Paint
## EXQT50

APPLY A HIGHER STANDARD®

URETHANE ACRYLIC™ | EG-FREE® Formulated without Ethylene Glycol or other TAC/HAP chemical | MILDEW INHIBITOR | green wise® CERTIFIED BY COATINGS RESEARCH GROUP INCORPORATED

≤ 50 g/L VOC**

## PRODUCT INFORMATION

### PRIMERS

**DRYWALL**

| | |
|---|---|
| Textured: | **VINYLASTIC® Premium (VNPR00),** |
| Untextured: | **VINYLASTIC® Premium (VNPR00),** |
| Skim-coated: | **VINYLASTIC® Plus (VNPL00)** (see Special Instructions) |

**MASONRY**

| | |
|---|---|
| Plaster:<br>Tilt-up concrete:<br>Poured-in-place:<br>Brick: | **EFF-STOP® Premium (ESPR00),**<br>**EFF-STOP® Select (ESSL00)** or<br>**FLEX-PRIME® Select (FPSL00)** |
| Concrete block: | **Smooth BLOCFIL™ Premium (SBPR00)** or<br>**Smooth BLOCFIL™ Select (SBSL00)** |
| Smooth trowel: | **SUPER-LOC® Premium (SLPR00)** |

**WOOD**

| | |
|---|---|
| Doors, trim | **DECOPRIME® (DCPR00)** or,<br>**ULTRA-GRIP® Premium (UGPR00)** |

**SYNTHETIC WOOD**

| | |
|---|---|
| Masonite:<br>Hardboard: | **DECOPRIME® (DCPR00)** |

**METAL**

| | |
|---|---|
| Ferrous: | **BLOC-RUST® Premium (BRPR00)** or<br>**ENDURAPRIME® Rust-Preventative Metal Primer (ENPR00)** |
| Non-ferrous: | **ENDURAPRIME® Galvanized Metal Primer (ENGM00),**<br>**BLOC-RUST® Premium (BRPR00)** or<br>**SUPER-LOC® Premium (SLPR00)** |
| Galvanized steel: | **ENDURAPRIME® Galvanized Metal Primer (ENGM00)** or<br>***ULTRA-GRIP® Premium (UGPR00)** |

**for incidental use on galvanized*

***This product has been tested and certified by Coatings Research Group Inc., an international paint industry-organized ISO-accredited testing laboratory, to meet performance and environmental standards as shown on www.greenwisepaint.com. Dunn-Edwards is a member of CRGI.*

**HEALTH & SAFETY: CAUTIONS!** INHALATION OF SPRAY MIST OR SANDING DUST MAY BE HARMFUL. Use only with adequate ventilation. Avoid breathing vapors, spray mist and sanding dust. Wear NIOSH-approved N100 particulate filter mask when spraying or sanding. Avoid contact with skin and eyes. Do not ingest. Close container after each use. **FIRST AID:** If swallowed, immediately give 1 or 2 glasses of water to drink – for emergency information, call 1-800-222-1222. If having difficulty breathing, move to fresh air. For eye contact, immediately flush with water for 15 minutes. For skin contact, wash thoroughly with soap and water.

**• KEEP OUT OF REACH OF CHILDREN •**

Ingredient (CAS #): Water (7732-18-5); Copolymer Resin (Proprietary); Titanium Dioxide (13463-67-7); Propylene Glycol (57-55-6); Synthetic Amorphous Silica (7631-86-9).

⚠ **WARNING!** Cancer and Reproductive Harm – www.P65Warnings.ca.gov