

CS 892 CONCEPTS PROFESSIONAL 100% Acrylic Paint Exterior Use

A 100% acrylic professional paint for masonry surfaces such as plaster, concrete, stucco, brick, as well as for wood. It combines excellent durability, rapid dry and ease of application. Dries to breathable coating that resists blistering.




Performance Features

- Flat finish with good durability.
- Breathable, blister-resistance coating.
- Easy application and clean up, quick recoat.
- Quality professional coating.

Colors : White and over 3500 tinted colors.

Toxicity: Formulated without lead or mercury

Gloss Level: 0-5 at 60° viewing angle.



Performance Guide:

Weather Resistance

Good resistance to weather, to chalking and dirt pick-up.

Environmental Resistance

Provides good resistance to concrete carbonation.

VICTORY 2002 has R(CO₂) > 50m when properly applied.

Heat Resistance

Softens above 60°C.

Water Resistance

Resists rain and condensation.

Abrasion Resistance

Good resistance to abrasion.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydro carbons and alcohols.



VOC (Volatile Organic Compounds): EU limit value for this product category A/c type WB: exterior walls of mineral substrate, 40g/l (2010). This product contains max 29g/l VOC.

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
10 – 11 m ² /L	49%	110 micrometres	49 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	Passes 6 mm mandrel	5% water	Brush, Roller, Spray

Surface Preparation

Surface to be painted must be free of all loose material such as flaking and peeling paint, dust, concrete salts and heavy chalk. The surface must be clean with all traces of grease, oil and dirt removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish. Apply two coats of CS 892 CONCEPTS PROFESSIONAL Acrylic Paint after priming the surface with CS 895 CONCEPTS PROFESSIONAL Acrylic Stabilizing Primer.

Wood Surfaces: with CS 023 THE PERFECT PRIMER All-purpose Eco Primer or CS 570 THE PERFECT PRIMER Alkyd Multi-Primer

Application

Stir paint thoroughly before use. Apply by roller, brush, or airless spray. Thin 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer under cool/moist conditions.

Clean Up:

Clean equipment in warm, soapy water promptly after painting.

Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes : 0,75 litre, 3 litres, 9 litres Flash Point: none Storage: not hazardous, no special requirements

