

WALL PLUS Solventborne Waterproofing Stabilizing Primer Interior/Exterior CS 182



A pigmented, solvent acrylic-based product for priming and waterproofing concrete and masonry surfaces. Penetrates fresh or aged masonry, concrete, plaster, and bricks to seal the surface. Adds Water Resistance to the coating system. Binds thin, powdery films. Use under emulsion paints, masonry paints and waterproofing elastomeric roof and wall paints. CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer has outstanding adhesion.


Performance Features

- Penetrates to seal the surface.
- Adds Water Resistance.
- Stabilises loose, powdering concrete.
- Prepares cellulose coatings for repaint.
- Use on exterior and interior porous surfaces.

Colors : White. May be tinted to light colors.

Toxicity: Formulated without lead or mercury

Gloss Level: Low sheen when applied on porous surfaces.



Performance Guide:

Weather Resistance

Good resistance to weathering.

Environmental Resistance

Good resistance to weather when topcoated with Colorstyle Paint
100% acrylic finishes.

Heat Resistance

Thermoplastic. Softens above 65° C .

Water Resistance

Good resistance to rain and condensation.

Abrasion Resistance

Good resistance to abrasion.

Solvent Resistance

Good resistance to white spirits, alcohols, aromatic hydrocarbons and other strong solvents.



VOC (Volatile Organic Compounds): This product belongs to the category A/h SB: Binding Primers. Ready to use product contains maximum 749g/L which is under the relevant EU limit values: 750g/l (2010).

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
8-9 m ² /L on porous surfaces	23%	74 micrometres	30 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
2 hours to touch 3-4 hours to recoat	Passes 3mm mandrel	White spirit.	Brush, Roller , Spray

Surface Preparation

Surface to be painted must be free of all loose material such as flaking and peeling paint, dust, concrete salts and heavy chalk. The surface must be clean with all traces of grease, oil, and dirt removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish. Apply one coat of CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer.

Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin as needed up to 100% with white spirits. For roofs, or where increased Water Resistance is desired, only thin up to 25%. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

Clean Up: Clean brushes and equipment with white spirit.

Precautions Health, Safety and Environmental Protection:

CAUTION. Contains - Naphtha (petroleum), heavy hydrogenated. • Flammable liquid and vapour. • May cause drowsiness or dizziness. • Harmful to aquatic life with long lasting effects. • Repeated exposure may cause skin dryness or cracking. • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. • Do not get in eyes, on skin, or on clothing • Wear protective gloves, protective clothing, eye protection, face protection. • IF INHALED: Remove person to fresh air and keep comfortable for breathing. • Call a POISON CENTER, doctor if you feel unwell. • Keep out of reach of children. • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Keep cool. • In case of fire: use carbon dioxide, foam, chemical powder to extinguish. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777



Packaging and Storage

Sizes : 1 litre, 3 litres, 10 litres

Flash Point: 44°C (Abel)

Storage: PAINTS, flammable liquid

