

Select Bath and Spa Satin Finish CS 322

A high quality 100% acrylic enamel for use in kitchens and bathrooms as well as other areas. Designed to have good adhesion over clean, hard surfaces and to resist the formation of mildew that moist or humid conditions can promote. Its spatter-resistant formula is odourless and easy to apply. CS 322 SELECT B&S is ideal for use as self primer on previously painted surfaces to light colors.




Performance Features

- For kitchens, bathrooms, laundries and inside areas subject to humidity, water splash and frequent cleaning.
- Contains a mildewcide to control fungal growth.
- Spatter resistance application.
- Good adhesion to new and previously painted surfaces.

Colors: White. May be tinted to light colors.

Toxicity: Formulated without lead or mercury

Gloss Level: 20 -25 at 60 degree viewing angle.



Performance Guide:

Weather Resistance

No recommended for exterior use.

Heat Resistance

Up to 65° C.

Water Resistance

Excellent Water Resistance. Not for immersion service.

Abrasion Resistance

Good resistance to abrasion.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30g/l (2010). This product contains max 29g/l VOC

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
11 - 15 m ² /L	34%	72 micrometres	24 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
2 hours to touch 8 hours to recoat	Passes 6mm mandrel	5% water	Brush, Roller, Spray

Surface Preparation

Surface to be painted must be clean and free of dirt, dust, grease, wax, loose material or flaking paint, and mildew. Clean hard or previously painted surfaces thoroughly with detergent and water. Rinse well. Remove loose material by scraping and sanding.

Note: If mildew is present, remove with a commercial mildew wash, following manufacturer's directions and cautions. Apply two coats of CS322 SELECT B&S after priming as outlined below.

New Walls, Gypsum Board and Plaster: Prime with CS 023 The Perfect Primer All-purpose Eco Primer

Previously Painted Surfaces: Ensure surfaces are thoroughly clean. Apply two coats of CS322 SELECT B&S

Wood: Prime with CS 023 The Perfect Primer All-purpose Eco Primer

Application

Stir paint thoroughly before use. Apply by brush, roller or spray. Thin 5% with clean water. Do not apply at temperatures below 10°C.

Drying times are longer in cool/moist conditions.

Clean Up: Clean equipment in warm, soapy water promptly after painting.

Precautions Health, Safety and Environmental Protection

•If medical advice is needed, have product container or label at hand. •Keep out of reach of children. •Keep container tightly closed. •Do not get in eyes, on skin, or on clothing. •Avoid release to the environment. •Call a POISON CENTER or a doctor if you feel unwell. •Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. •Safety data sheet available on request. •Contains: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-Benzisothiazol-3 (2H) -one, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, 3-Iodo-2-propynyl N-butylcarbamate. May produce an allergic reaction. •Contains a biocidal product with fungicidal & algicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6), 2-octyl-2H-isothiazol-3-one (26530-20-1) and zinc pyrithione (13463-41-7) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters.

POISON CENTER TEL.: +302107793777

Packaging and Storage

Sizes : 1 litre, 3 litres,

Flash Point: none

Storage: not hazardous, no special requirements

