

THE PERFECT PRIMER Stain Killer Waterborne Primer & Sealer CS 341

A fast drying 100% acrylic sealer and stain suppressor with normal drying time of 30 minutes, which allows quick recoat. Specially formulated to prime and seal stained surfaces such as smoke, water stains, lipstick, crayon, nicotine and others. Good stained blocking on tropical wood on interior use. Use on walls, plaster, gypsum, board, wood. Breathable film, outstanding adhesion and sealing.




Performance Features

- Fast drying 30 minutes allows recoat same day.
- Excellent holding back stains.
- Gives a smooth surface for quality finish.
- Easy clean up with soap and water.

Colors : White. May be tinted to light colors for additional hiding.

Toxicity: Formulated without lead or mercury

Gloss Level: Satin.



Performance Guide:

Weather Resistance

Excellent resistance when topcoated with Benjamin Moore exterior finishes.

Heat Resistance

Up to 60° C.

Water Resistance

Excellent Water Resistance.

Abrasion Resistance

Good resistance to abrasion.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydro carbons and alcohols.



VOC (Volatile Organic Compounds): EU limit value for this product category A/g type WB: Primers, 30g/l (2010). This product contains max 29g/l VOC.

Spreading Rate

12 – 15 m²/L

Volume Solids

47%

Wet Film Thickness

85 micrometres

Dry Film Thickness

40 micrometres

Dry Time at 20°C

30 minutes to touch
2 hours to recoat

Flexibility

6mm mandrel

Thinning

5% water

For Application By

Brush, Roller, Spray

Surface Preparation

Surface must be free of all loose material such as flaking and peeling paint, dust, dirt and heavy chalk. The surface must be clean from grease, form oils, and mildew removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish.

NOTE: If mildew is present, remove with a commercial mildew wash following manufacturer's directions and cautions. Fill nail holes, cracks and areas needing repair, then spot prime these areas. After drying apply one or two coats of CS 341 THE PERFECT PRIMER Stain Killer Primer & Sealer.

New surface: Apply one coat of CS 341 THE PERFECT PRIMER Stain Killer Primer & Sealer.

Previously Painted Surfaces: Spot prime any repairs, then apply an overall – coat of CS 341 THE PERFECT PRIMER Stain Killer Primer & Sealer.

Wood: Spot prime any repairs, then apply an overall coat of CS 341 THE PERFECT PRIMER Stain Killer Primer & Sealer.

Stained Surfaces: Two coats of CS 341 THE PERFECT PRIMER Stain Killer Primer & Sealer are recommended for tough stains.

Application

Stir paint thoroughly before use. Apply by roller, brush or airless spray. Thinning 5% with water. Do not apply at temperatures below 10° C.

Clean Up:

Clean equipment in warm, soapy water.

Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes : 0,75 litre, 2,5 litres

Flash Point: none

Storage: not hazardous, no special requirements

