

THE PERFECT PRIMER Alkyd Multi-Primer & Sealer CS 570



A pigmented, alkyd-based, multi-purpose primer for use on plaster walls and wood, and as an intermediate coat on primed metal and previously painted surfaces. It suppresses stains, has outstanding adhesion, high opacity and easy sanding. Can be used under both acrylic and enamel Wood & Metal topcoats. Formulated without lead.


Performance Features

- Multiple uses.
- Outstanding adhesion.
- Completely seals porous surfaces.
- Gives a smooth surface for a quality finish.
- Use on interior or exterior surfaces.
- Suitable for high use or commercial areas.

Colors: White. May be tinted to light colors.

Toxicity: Formulated without lead or mercury.

Gloss Level: Low sheen.



Performance Guide:

Weather Resistance

Excellent when topcoated with Colorstyle Paint exterior finishes.

Heat Resistance

Up to 120°C. Continuous heat will cause premature yellowing and embrittlement.

Water Resistance

Good resistance to water and condensation.

Solvent Resistance

Good resistance to aliphatic solvents and alcohols. Sensitive to aromatic hydro carbons and other strong solvents.



VOC (Volatile Organic Compounds): This product belongs to the category A/g SB: Primers. Ready to use product contains maximum 349g/L which is under the relevant EU limit values: 350g/l (2010).

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
13 – 14 m ² /L	40%	77 micrometres	31 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
3 hours to touch 16 hours to recoat	Passes 3mm mandrel	5% white spirits	Brush, Roller, Spray

Surface Preparation

Surface to be painted must be free of all loose material such as dust and peeling paint. The surface must be clean with all traces of grease, oil and dirt removed. Remove loose material by scraping and sanding. Sand glossy surfaces to a dull finish.

Plaster Walls, New or Previously Painted Wood, Primed or Previously Painted Metal: Apply one coat CS 570 THE PERFECT PRIMER Alkyd Multi-Primer & Sealer.

Stained Surfaces: Apply one or two coats CS 570 THE PERFECT PRIMER Alkyd Multi-Primer & Sealer.

Ferrous Metal: Must be primed. Use CS 568 THE PERFECT PRIMER Alkyd Rust Primer, following label directions.

Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Thin 5% with white spirits. Do not apply when air or surface temperature is below 10°C or when the humidity is high. Drying times are longer under cool/moist conditions.

Clean Up: Clean brushes and equipment with white spirits.

Precautions Health, Safety and Environmental Protection:

CAUTION. Contains - Naphtha (petroleum), heavy hydrogenated • Flammable liquid and vapour. • Harmful to aquatic life with long lasting effects. • Repeated exposure may cause skin dryness or cracking • May cause drowsiness or dizziness. IF INHALED: Remove person to fresh air and keep comfortable for breathing • Contains cobalt bis(2-ethylhexanoate) And 2-Butanone oxime. May produce an allergic reaction • Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. • No smoking. • Do not get in eyes, on skin, or on clothing • Wear protective gloves, protective clothing, eye protection, face protection. • Call a POISON CENTER, doctor if you feel unwell. • Keep out of reach of children. • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Keep cool. • In case of fire: use carbon dioxide, foam, chemical powder to extinguish. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777



Packaging and Storage

Sizes : 0,75litre, 2,5 litres

Flash Point: 44°C (Abel)

Storage: PAINTS, flammable liquid



For Advising – Technical Services call: 2106620713-5